



Compact wall speaker matrix

Overview

											
	ATEO2	ATEO4	ATEO6	WX302	WX502	WX802	XENO6	XENO8	KYDO	AXIR	GIAX
Frequency Range (-10 dB)	100 Hz - 20 kHz	65 Hz - 20 kHz	55 Hz - 20 kHz	60 Hz - 20 kHz	55 Hz - 20 kHz	50 Hz - 20 kHz	55 Hz - 20 kHz	50 Hz - 20 kHz	80 Hz - 19 kHz	80 Hz - 19 kHz	80 Hz - 19 kHz
Max SPL	93 dB	101 dB	106 dB	100 dB	104 dB	108 dB	110 dB	110 dB	106 dB	113 dB	114 dB
Max power handling	20W	70W	120W	60W	100W	140W	160W	240W	120W	240W	480W
Woofer size	2"	4"	6"	3"	5"	8"	6"	8"	2"	2"	2"
Outdoor				✓*	✓*	✓*				✓*	
100V		3W / 6W / 12W / 24W	6,25W / 12,5W / 25W / 50W	5W / 10W / 20W	10W / 20W / 40W	15W / 30W / 60W			2,5W / 5W / 10W / 20W	2,5W / 5W / 10W / 20W**	
Impedance	8 / 16 Ohm	8 / 16 Ohm	8 / 16 Ohm	8 Ohm	8 Ohm	16 Ohm	8 Ohm	8 Ohm	12 Ohm	6 Ohm	4 Ohm
CleverMount™	✓	✓	✓								
AWX5™ Connector				✓*	✓*	✓*				✓*	

* The AUDAC WX/O and AXIR/O speakers are specifically designed for outdoor use and lend themselves to a variety of outdoor applications.

** Line Transformer Tappings AXIR/O: 5W / 10W / 20W