






















# Flush mount loudspeakers

## Overview

																			
Frequency Range (-10 dB)	100 Hz - 20 kHz	55 Hz - 20 kHz	44 Hz - 20 kHz	32 Hz - 20 kHz			80 Hz - 18 kHz	70 Hz - 18 kHz	60 Hz - 18 kHz	45 Hz - 20 kHz	45 Hz - 20 kHz	33 Hz - 20 kHz	70 Hz - 20 kHz	65 Hz - 20 kHz	80 Hz - 18 kHz	55 Hz - 20 kHz	100 Hz - 20 kHz	55 Hz - 20 kHz	44 Hz - 20 kHz
Max SPL	93dB	102dB	106dB	108dB	103dB	97dB	103dB	106dB	112dB	102dB	103dB	105dB	101dB	106dB	95dB	99dB	93dB	102dB	106dB
Max power handling	20W	100W	120W	160W	2 x 100W	20W	20W	20W	40W	60W	60W	80W	60W	120W	10W	40W	20W	100W	120W
Closed back	✓												✓	✓	✓		✓		
Outdoor										✓*	✓*	✓*	✓*	✓*	IP65	IP44			
100V	1,5W / 3W / 6W**	6W / 12W / 24W**	6W / 12W / 24W**	6W / 12W / 24W**		3W / 6W	3W / 6W	3W / 6W	6W / 12W	6W / 12W / 24W***	6W / 12W / 24W	6W / 12W / 24W	6W / 12W / 24W	15W / 30W / 60W	1,5W / 3W / 6W		1,5W / 3W / 6W**	6W / 12W / 24W**	6W / 12W / 24W**
Impedance	8 / 16 Ohm	8 Ohm	8 Ohm	8 Ohm	8 Ohm	8 Ohm	8 / 16 Ohm	8 / 16 Ohm	8 / 16 Ohm	8 / 16 Ohm	8 / 16 Ohm	8 / 16 Ohm	8 Ohm	8 Ohm	8 Ohm	8 Ohm	8 / 16 Ohm	8 Ohm	8 Ohm
SpringFit™						✓	✓	✓	✓						✓				
QuickFit™	✓	✓	✓	✓	✓					✓	✓	✓					✓	✓	✓
SafeLatch™													✓	✓					
Cutout hole size	Ø100 mm	Ø155 mm	Ø205 mm	Ø245 mm	Ø250 mm	Ø80 mm	Ø150 mm	Ø167 mm	Ø207 mm	Ø170 mm	Ø200 mm	Ø243 mm	Ø170 mm	Ø220 mm	Ø125 mm	Ø120 mm	128x80 mm	139x214 mm	174x254 mm
Dispersion	165°	155°	140°	135°		160°	155°	140°	130°	145°	150°	140°	155°	145°			165°-165° (Hor.-Vert.)	160°-140° (Hor.-Vert.)	160°-140° (Hor.-Vert.)

\* CIRA and CALI optional GLI series grills are outdoor treated. This makes the speakers suitable for dry outdoor installation, the speakers are not splash nor waterproof.

\*\* With addition of WTR06 (1,5W / 3W / 6W) or WTR24 (6W / 12W / 24W) Waterproof Transformer 100V.

\*\*\* Line Transformer Tappings CIRA506: 1,5W / 3W / 6W